

DATA SHEET.

INDUSTRIAL VACUUM.

IWV 80



G. Staehle GmbH u. Co. KG
Mercedesstraße 15
D 70372 Stuttgart
Telefon +49 (0) 7 11/95 44-950
Telefax +49 (0) 7 11/95 44-941
info@columbus-clean.com
www.columbus-clean.com

columbus

FOR ALL LIQUIDS:

IWV 80

- Compact wet vacuum for many industrial applications.
- Safety cut-out when the container is full.
- Controlled emptying with drain hose.
- Two individually switchable bypass suction motors.
- Made of robust, epoxy-coated steel. Non-marking rollers and locking brake for safety and comfort while emptying.



Bypass motors

With the bypass motor, the suction air flow is not also used to cool the motor. The motor is cooled with a separate air flow. This stops the motor overheating when cleaning hot dusts for example.

Applications:
For various wet applications in
virtually all industrial sectors



Drain hose from container



Accessories kit for IWV 80



Optional rubber suction tool



Effective removal of liquids with
the floor tool

IWV 80

L x B x H	530x660x1080 mm mm
Tool connection	80 mm
PVC hose	PVC 3 m/50 mm
Container volume	80 l
Filter surface area	-
Filter type	Polyester cartridge
Filter dust class	-

ELECTRICAL DATA

Rated voltage	230 V
Rated power, total	2,3 KW
Mains cable	10 m

SUCTION MOTOR

Negative pressure, max.	2500 mm.H ₂ O
Air flow, max.	360 M ³ /h
Number of motors	2