

DATA SHEET.

WET AND DRY VACUUM CLEANER.

SW32IP



G. Staehle GmbH u. Co. KG  
Mercedesstraße 15  
D 70372 Stuttgart  
Telefon +49 (0) 7 11/95 44-960  
Telefax +49 (0) 7 11/95 44-941  
export@columbus-clean.com  
www.columbus-clean.com

**columbus**

# CLEANING ON THE MOVE: THE HIGH SUCTION COMPACT CLASS.

## SW 32IP

- With a capacity of 30 litres, a powerful motor and integrated air flow regulation, the wet and dry vacuum cleaner is ideally suited for cleaning small- to medium-sized surfaces.
- Air slots ensure a strict separation of the cooling air and vacuum circuit.
- 400 mm combined nozzle – the perfect width for professional use for both wet and dry applications.
- The cyclone system ensures optimum protection of the motor by controlling the flow of the dirty water. The floater responds reliably in case of foaming.
- With the integrated blow-out function, filters and filter cages can be cleaned easily. It is particularly well-suited for removing dust and dust particles from workbenches or to dry wet surfaces.
- The wet vacuum cleaner made of shock-proof PP materials is robust and manoeuvrable thanks to the two large wheels and castors.
- Ergonomic, fast and flexible due to the rotatable suction hose insert.
- The vacuum cleaner can be easily turned on and off with a foot switch. The suction accessories may be stored ready to hand on the rear.

The cyclone system ensures optimum protection of the motor by controlling the flow of the dirty water. The floater responds reliably in case of foaming.

Kompakt und alles griffbereit.



### SW 32IP

|               |                |
|---------------|----------------|
| L x B x H     | 430x360x580 mm |
| Working width | 400 mm         |
| Suction hose  | 2,5 m          |
| Tank capacity | 30 l           |
| Noise level   | 70 dB(A)       |
| Weight        | 7,8 kg         |

### ELECTRICAL DATA

|               |        |
|---------------|--------|
| Rated voltage | 230 V  |
| Power max.    | 1300 W |
| Mains cable   | 10 m   |

### SUCTION MOTOR

|                    |          |
|--------------------|----------|
| Low pressure, max. | 260 mbar |
| Air flow, max.     | 56 l/s   |
| Number of motors   | 1        |