

WET AND DRY VACUUM CLEANER.

30 UP TO 78 LITRES.



**columbus**

# CLEANING ON THE MOVE: THE HIGH SUCTION COMPACT CLASS.

SW 30|P  
SW 30|S  
SW 50|P  
SW 50|S

- Well equipped for basic cleaning, initial construction cleaning or use in workshops: wet & dry vacuum cleaners with compact vacuum tanks made of impact-resistant plastic (P) or chromium steel (S).
- Robust and sturdy design: secure positioning and convenient transport every time.
- Extensive range of professional accessories: a roller-guided wet suction tool as well as additional accessories for dry and wet cleaning are series-standard and included in delivery. A large assortment of special extras is also available.
- Hygienic dry cleaning: the specially pre-treated sanifilter cloth bag – series-standard for the SW 30 to SW 53 wet and dry vacuum cleaners – prevents the growth of bacteria, viruses, fungi (yeasts and mould) and microparasites that have been vacuumed up.



SW 30|P  
SW 30|S

- The handy, compact and mobile single-motor all-rounder with 32 or 35-litre tank capacity for professional use on small surfaces.

SW 50|P  
SW 50|S

- The single-motor expert for longer operating times without emptying the tank: 62 or 72-litre capacity for medium to large surfaces.
- Easy to empty: the drain hose situated at the lowest point of the tank allows the dirty water to be emptied completely and conveniently.



# CLEAN DESIGN: THE PROFESSIONAL CLASS FOR THE TOUGHEST TASKS.

SW 52|P

SW 52|S

SW 53|P

SW 53|S

- Real professionals: the SW 52 wet and dry vacuum cleaner with two motors and the SW 53 with three for medium to large surfaces.
- Strong suction – wet or dry: for impressive results for a variety of hose lengths, the motors can be switched on and off individually.
- Coarse dirt is easy: the powerful suction capacity in connection with robust and high-quality vacuum hoses with a diameter of 38 mm allow even larger debris to be vacuumed up easily.
- Quick and clean: thanks to the ample tank with 72 and 78 litres, both models can vacuum up large amounts of dirt and liquid with ease. The vacuum tanks can be emptied quickly and conveniently using the tilting device or the drain hose.



# SINGLE OR MULTIPLE MOTOR. ALWAYS A CLEAN PERFORMANCE.

	SW 30 P	SW 30 S	SW 50 P	SW 50 S
L x B x H	4450x450x820 mm	430x430x830 mm	570x570x1030 mm	520x520x960 mm
Working width	400 mm	400 mm	400 mm	400 mm
Suction hose	2,5 m	2,5 m	2,5 m	2,5 m
Tank capacity	35 l	32 l	72 l	62 l
Noise level	77,4 dB(A)	73,4 dB(A)	73,4 dB(A)	73,4 dB(A)
Weight	13 kg	13 kg	20 kg	19 kg

## ELECTRICAL DATA

Rated voltage	230 V	230 V	230 V	230 V
Power max.	1200 W	1200 W	1200 W	1200 W
Mains cable	12 m	12 m	12 m	12 m

## SUCTION MOTOR

Low pressure, max.	240 mbar	240 mbar	240 mbar	240 mbar
Air flow, max.	58 l/s	58 l/s	58 l/s	58 l/s
Number of motors	1	1	1	1

	SW 52 P	SW 52 S	SW 53 P	SW 53 S
L x B x H	650x590x1050 mm	650x590x1050 mm	650x590x1050 mm	650x590x1050 mm
Working width	400 mm	400 mm	400 mm	400 mm
Suction hose	2,5 m	2,5 m	2,5 m	2,5 m
Tank capacity	72 l	78 l	72 l	78 l
Noise level	80,5 dB(A)	80,5 dB(A)	81,5 dB(A)	81,5 dB(A)
Weight	29,5 kg	30 kg	32 kg	32,5 kg

## ELECTRICAL DATA

Rated voltage	230 V	230 V	230 V	230 V
Power max.	2400 W	2400 W	3300 W	3300 W
Mains cable	12 m	12 m	12 m	12 m

## SUCTION MOTOR

Low pressure, max.	240 mbar	240 mbar	240 mbar	240 mbar
Air flow, max.	116 l/s	116 l/s	175 l/s	175 l/s
Number of motors	2	2	3	3

Technical data subject to change without notice.